



# 3 PLY

## Flute Laminator

This machine adopts motion control system and servo correction system, using multiple sets of photoelectric sensors at the end of the paper the relative position.

It is equipped with 8 servo motors, and what makes it differ from the normal automatic type is that the convey bridge for the top sheet is lengthened to be 1.5m, where lies several pulling-balls (correction unit), thus the fitness is very accurate.

Servo laminating machine has the advantages of simple operation, we only need to input the size of paper and the machine would adjust the feeder, the bottom feeding and the pressure system automatically, which realizes the intelligent operation.

| Model                  | IC FG 3-1450            | IC FG 3-1700            |
|------------------------|-------------------------|-------------------------|
| Max Paper Size         | 1450x1450mm             | 1700x1450mm             |
| Min Paper Size         | 360x360mm               | 360x360mm               |
| Paper Thickness        | 180-800g/m <sup>2</sup> | 180-800g/m <sup>2</sup> |
| Paper Bottom Thickness | 0.5-10mm(A-F)           | 0.5-10mm(A-F)           |
| Machine Speed          | 160m/min                | 160m/min                |
| Laminating Precisin    | ±1.5mm                  | ±1.5mm                  |
| Total Power            | 16KW                    | 17KW                    |
| Weights                | ≈6.7T                   | ≈7.5T                   |
| Machine Size           | 14500Lx2400Wx2600H      | 15000Lx2650Wx2600H      |



## Contact Us

+91 72192 90087 / +91 84593 79203

[sales@integriticonsulting.in](mailto:sales@integriticonsulting.in)

[www.integriticonsulting.in](http://www.integriticonsulting.in)