

PLASMA TREATMENT FOR FOLDER GLUER



■ PLASMA SURFACE TREATMENT EQUIPMENT

Model	ICPL-1	ICPL-2
Head Number	1	2
Touch Screen	4.3 inch	
Input voltage	200-240 Vac	
Voltage Frequency	50-60 HZ	
Input current	≤7.5 A	≤ 15 A
Max Output Power	1000W *1	1000W *2
Input Air Pressure	2-4 bar	
Air flow	60 L/min	120 L/min
Excitation frequency	20~30 KHZ	
Handling width	5~10 mm	5~10 mm *2
Head cable length	2.5 m	
Power cable	3*1.5	3*2.5
Dimensions	450*225*150	
Weight	24	34



Model	ICPL-1	ICPL-2	ICPL-3
Head Number	1	2	3
Touch Screen	4.3 inch		
Input voltage	200-240 Vac		
Voltage Frequency	50-60 HZ		
Input current	≤7.5 A	≤ 15 A	≤ 23 A
Max Output Power	1000W *1	1000W *2	1000W *3
Input Air Pressure	2-4 bar		
Air flow	60 L/min	120 L/min	180 L/min
Excitation frequency	20~30 KHZ		
Handling width	5~10 mm	5~10 mm *2	5~10 mm *3
Head cable length	2.5 m		
Power cable	3*1.5	3*2.5	3*2.5
Dimensions	700*350*1010		
Weight	38	48	58



CONTACT US

-  +91 72192 90087 / +91 84593 79203
-  sales@integriticonsulting.in
-  www.integriticonsulting.in